

Engine	
Manufacturer/make	MTU OM-460 LA
Engine type	L6
Output, kW (hp)	368 (500)
Fuel tank	1 080 (2*540)
Air compressor	●
Fuel consumption metering	●
Feeding unit (intake)	
Width, mm	680
Number of feedrolls	4
Reverse	mechanical
Metal detector	●
Stone detector	●
Stone detector with auto start	●
Chopping system	
Diameter/length, mm	630/700
Number of knives	24 (V-form configuration)
Rotation speed, rpm	1 200
Automatic sharpening system	●
Automatic bar adjustment	●
Cutting length, mm	4/ 7/ 10/ 17
Manual cutting length	adjustment by reducer
Automatic central lubricating system	●
Corn Cracker	●
Type	toothed feedrolls
Feedroll diameter, mm	190
Rotation speed difference, %	20
Unloading unit	
Accelerators rotor diameter, mm	510
Rotor speed, rpm	2 160
Silage duct turning angle, deg.	226
Preservative applicator	●
Preservative tank capacity, l 5x2	●
Water tank capacity, l 390	●
Video control system (unloading chute and rear view)	●
Chassis	
Transmission	hydrostatic power
Traveling speed, km/h,	up to 20
Operating speed, km/h,	up to 15
Clearance, mm	367
4WD	○
Cab	
Comfort Cab ¹	●
Adviser III ² information system	●
Overall dimensions (without header)	
Length/width/height, mm	6 170/3 250/3 800
Weight without adapter, kg	9 900
Adapters	
Corn header, m	4,5 (6 rows) and 6,0 (8 row)
Grass header, m	5,0
Windrow pickup, m	3,0

● standard ○ option

¹ **Comfort Cab** - spring-mounted airtight two-seat cab with improved noise insulation, air conditioner, heater, refrigerator and audio system² **Adviser III** information system with LCD monitor, situational framing and voice announcement.